




ARRANGE METHOD:



**Remark:**  
 ① Cable: Cat.5E UTP, Stranded Bare Copper, 4Pairs Wires, 24AWG, Jacket PVC, OD: 5.5mm.  
 ② Plug: Cat.5 Unbreakable Unshielded Type Plug with 2 Prongs, 50u", 8P8C, UL94-V2, Mating Cycle >1200.  
 ③ Packing: 1PC/PE Bag with Label.  
 Testing: 100% Continuity Test. (Component test Optional).  
 All materials are RoHS compliant.



CUT LINE AND ARRANGE CRITERION				CUT LINE AND ARRANGE CRITERION			
No.	Total length (MM)	no of patch cord (MM)	Cable tie (MM)	No.	Total length (MM)	no of patch cord (MM)	Cable tie (MM)
1	300	A	/	19	13000	B	175
2	500	/	/	20	14000	/	160
3	1000	/	/	21	15000	/	205
4	1500	175	60	22	16000	/	210
5	2000	/	70	23	17000	/	215
6	2500	/	75	24	18000	/	220
7	3000	165	80	25	19000	/	225
8	3500	/	85	26	20000	/	235
9	4000	/	95	27	25000	120	265
10	5000	/	100	28	30000	/	315
11	6000	/	110	29	40000	/	365
12	7000	/	120	30	50000	/	415
13	7500	135	135	31	60000	/	465
14	8000	/	140	32	70000	/	515
15	9000	/	145	33	80000	/	565
16	10000	/	150	34	90000	/	615
17	11000	120	165	35	100000	/	665
18	12000	/	170	36	/	/	/

WIRE CONNECTION TABLE								LENGTH		MOLD NO.	
	white/ orange	white/ green	blue/ blue	white/ blue	green/ brown	white/ brown		(4+50)1(100)1(190)1		02-008	
A1	A2	A3	A4	A5	A6	A7	A8				
B1	B2	B3	B4	B5	B6	B7	B8				

DWG. NO. PSEUTTB008-001			
TITLE CAT.5E UTP Unbreakable PATCH CORD			
UNIT mm			
SCALE 1/1		SHEET 1/1	
DRAWN DATE 2017/10/10		PROJ. CHECKED	
APPROVAL		DRAWN	
Carine		Wuming	
		CathyLi	